

Bushing Technical Specification Spreadsheet

Part Number	Rev Level	Rev Date	Length Range	Recommended Bore Diameter	OD Before Insertion		ID After Insertion		Chamfer Length		Standard Length Range & Tolerance			Mat'l Thk
					Min	Max	Min	Max	Min	Max	Min	Max	Tol	
075-050-XXX	1	16-Dec-16	1/2" - 1-3/4"	0.752/0.750	0.770	0.810	0.503	0.507	0.060	0.090	050	350	+/- 0.031	0.125
			2" - 3-1/2"					0.510						
087-062-XXX	2	07-Dec-16	1/2" - 1-3/4"	0.877/0.875	0.895	0.935	0.625	0.632	0.060	0.090	050	300	+/- 0.031	0.125
			2" - 3-1/2"					0.635						
087-075-XXX	1	07-Dec-16	1/2" - 1-3/4"	0.877/0.875	0.895	0.935	0.753	0.757	0.060	0.090	050	300	+/- 0.031	0.060
			2" - 3"					0.760						
100-062-XXX	1	07-Dec-16	1/2" - 1-3/4"	1.002/1.000	1.020	1.040	0.628	0.632	0.080	0.120	050	300	+/- 0.031	0.187
			2" - 3"					0.635						
100-075-XXX	1	06-Dec-16	1/2" - 1-3/4"	1.002/1.000	1.020	1.060	0.753	0.757	0.080	0.120	050	300	+/- 0.031	0.125
			2" - 3"					0.760						
100-082-XXX	1	05-Jan-17	1/2" - 1-3/4"	1.002/1.000	1.020	1.060	0.824	0.828	0.080	0.120	050	300	+/- 0.031	0.187
			2" - 3"					0.831						
112-075-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.126/1.125	1.145	1.185	0.753	0.757	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					0.760						
112-087-XXX	1	07-Dec-16	1/2" - 1-3/4"	1.126/1.125	1.145	1.165	1.145	1.185	0.875	0.882	050	300	+/- 0.031	0.125
			2" - 3"					1.185						
112-100-XXX	1	05-Jan-17	1/2" - 1-3/4"	1.126/1.125	1.145	1.185	1.145	1.185	1.000	1.007	050	175	+/- 0.031	0.125
			2" - 3"					1.185						
125-087-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.253/1.250	1.270	1.310	0.878	0.882	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					0.885						
125-100-XXX	1	06-Dec-16	1/2" - 1-3/4"	1.253/1.250	1.270	1.310	1.003	1.007	0.080	0.120	050	300	+/- 0.031	0.125
			2" - 3"					1.010						
137-100-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.378/1.375	1.395	1.435	1.003	1.007	0.080	0.120	075	300	+/- 0.031	0.188
			2" - 3"					1.010						
137-112-XXX	1	07-Dec-16	1/2" - 1-3/4"	1.378/1.375	1.395	1.435	1.128	1.132	0.080	0.120	075	300	+/- 0.031	0.125
			2" - 3"					1.135						
150-100-XXX	1	07-Dec-16	1" - 1-3/4"	1.503/1.500	1.520	1.560	1.003	1.007	0.080	0.120	100	300	+/- 0.031	0.250
			2" - 3"					1.010						
150-112-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.503/1.500	1.520	1.560	1.125	1.132	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					1.135						
150-125-XXX	2	06-Dec-16	1/2" - 1-3/4"	1.503/1.500	1.520	1.560	1.253	1.257	0.080	0.120	050	300	+/- 0.031	0.125
			2" - 3"					1.260						
162-112-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.628/1.625	1.645	1.685	1.128	1.132	0.080	0.120	075	300	+/- 0.031	0.250
			2" - 3"					1.135						
162-125-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.628/1.625	1.645	1.665	1.253	1.257	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					1.260						
162-137-XXX	0	08-Apr-16	3/4" - 1-3/4"	1.628/1.625	1.640	1.680	1.378	1.382	0.080	0.120	075	300	+/- 0.031	0.125
			2" - 3"					1.385						
175-125-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.753/1.750	1.770	1.810	1.253	1.257	0.080	0.120	075	300	+/- 0.031	0.250
			2" - 3"					1.260						
175-137-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.753/1.750	1.770	1.810	1.378	1.382	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					1.385						
175-150-XXX	1	06-Dec-16	1/2" - 1-3/4"	1.753/1.750	1.770	1.810	1.503	1.507	0.080	0.120	050	300	+/- 0.031	0.125
			2" - 3"					1.510						
187-150-XXX	1	07-Dec-16	3/4" - 1-3/4"	1.878/1.875	1.895	1.935	1.503	1.507	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					1.510						
187-162-XXX	2	19-Mar-15	3/4" - 1-3/4"	1.878/1.875	1.895	1.935	1.628	1.632	0.080	0.120	075	300	+/- 0.031	0.125
			2" - 3"					1.635						
200-150-XXX	2	07-Dec-16	3/4" - 1-3/4"	2.004/2.000	2.020	2.060	1.504	1.512	0.100	0.150	075	300	+/- 0.031	0.250
			2" - 3"					1.516						
200-175-XXX	1	15-Dec-16	3/4" - 3"	2.004/2.000	2.020	2.060	1.750	1.757	0.080	0.120	075	300	+/- 0.031	0.125
			2" - 3"					1.760						
212-175-XXX	1	15-Dec-16	7/8" - 1-3/4"	2.128/2.125	2.145	2.185	1.753	1.763	0.080	0.120	087	300	+/- 0.031	0.187
			2" - 3"					1.763						
212-187-XXX	1	15-Dec-16	7/8" - 1-3/4"	2.128/2.125	2.145	2.185	1.878	1.882	0.080	0.120	087	300	+/- 0.031	0.125
			2" - 3"					1.885						
225-175-XXX	1	15-Dec-16	1" - 1-3/4"	2.254/2.250	2.270	2.310	1.753	1.757	0.080	0.120	100	300	+/- 0.031	0.250
			2" - 3"					1.760						
225-200-XXX	3	15-Dec-16	1" - 1-3/4"	2.254/2.250	2.270	2.310	2.004	2.012	0.080	0.120	100	300	+/- 0.031	0.125
			2" - 3"					2.016						
237-200-XXX	1	15-Dec-16	3/4" - 1-3/4"	2.379/2.375	2.406	2.446	2.004	2.012	0.080	0.120	075	300	+/- 0.031	0.187
			2" - 3"					2.016						
250-200-XXX	1	15-Dec-16	1" - 1-3/4"	2.504/2.500	2.530	2.570	2.004	2.012	0.100	0.150	100	300	+/- 0.031	0.250
			2" - 3"					2.016						
250-225-XXX	1	16-Dec-16	1" - 3"	2.504/2.500	2.520	2.560	2.250	2.266	0.080	0.120	100	300	+/- 0.031	0.125
			2" - 3"					2.266						
262-212-XXX	0	18-Sep-15	1" - 1-3/4"	2.629/2.625	2.645	2.685	2.129	2.137	0.100	0.120	100	300	+/- 0.031	0.250
			2" - 3"					2.141						
275-250-XXX	0	18-Sep-15	1" - 1-3/4"	2.754/2.750	2.770	2.810	2.504	2.512	0.080	0.120	100	300	+/- 0.031	0.125
			2" - 3"					2.516						
300-250-XXX	1	07-Dec-16	1" - 1-3/4"	3.004/3.000	3.030	3.090	2.504	2.512	0.100	0.150	100	300	+/- 0.031	0.250
			2" - 3"					2.516						
300-275-XXX	1	16-Dec-16	1" - 1-3/4"	3.004/3.000	3.030	3.090	2.754	2.762	0.100	0.150	100	300	+/- 0.031	0.125
			2" - 3"					2.766						
350-300-XXX	1	07-Dec-16	1" - 1-3/4"	3.505/3.500	3.532	3.590	3.005	3.013	0.100	0.150	100	300	+/- 0.031	0.250
			2" - 3"					3.019						
500-450-XXX	1	16-Dec-16	1" - 3"	5.005/5.000	5.030	5.110	4.500	4.519	0.100	0.150	100	300	+/- 0.031	0.250
			2" - 3"					4.519						